



# Liquid-O-Ring® \*

Your Super Center for over 1,000 top performance products serving industries worldwide.

## 165L Alumolon

Liquid-O-Ring®

Anti-Seize Compounds  
Drill Collar and Tool Joint Compounds  
Extreme Temperature Compounds  
Fish Net Coatings  
Greases  
  Bearing  
  Food Grade  
  High Temp  
  Low Temp  
  Multi-Purpose  
  Specialty  
  Silicone  
  Synthetic  
Oils  
  Compressor  
  Cutting  
  Forging Die Lube  
  Gear  
  Hydraulic  
  Motor  
  Penetrating  
  Silicone  
  Torsion  
  Transmission  
  Treatment  
Oilfield Production Products  
Pipe Storage Compounds  
Lubricants  
Sealants  
Pump Packings  
Thread Cleaner  
Thread Compounds  
  Biodegradable  
  High Temperature  
  Arctic Grade  
Thread Locking Compound  
Thread Sealants  
Valve Lubricants and Sealants  
Wireline Products  
  Protekto-Coat  
Internal and External Pipe Coatings  
  Low VOC  
  Biodegradable  
Corrosion Inhibitors  
  Speciality Items  
Cleaners and Degreasers

The product information and specifications listed in this publication are constantly being updated to keep up with government regulations and technology changes. Please visit our website, [www.oilcenter.com](http://www.oilcenter.com), or contact your Account Representative for the most current information relating to this product.

**WARRANTY** Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise. Each user should independently determine the suitability of this product based on their specific application.

### PRODUCT DESCRIPTION

**165L Alumolon** is a premium, multipurpose grease made with LIQUILON® for increased lubricity. LIQUILON offers the lowest coefficient of friction of any material on the market today.

**165L Alumolon** plates out on the surface allowing easy sliding thus using less electricity to run machine and tools. **165L Alumolon** can be used for both high and low temperature applications and is suitable for a variety of applications when mechanical shear resistance is a requirement. This water resistant grease contains inhibitors for protection against rust and oxidation.

### BENEFITS

**Made with Liquilon®\***  
**Excellent EP properties**  
**Excellent anti-wear properties**  
**Excellent stability**  
**Resists water washout**  
**Protects against rust and corrosion**  
**Protects against rust and corrosion**

### APPLICATION

**165L Alumolon** provides lubrication of automotive wheel bearings, chassis, all types of bearings, gears and couplings.

### TYPICAL OBSERVATIONS

Color	Yellowish Tan
Texture	Smooth
Thickener	Liquilon®*
Density, lb/gal @ 77°F (25°C)	7.40
Specific Gravity, @ 77°F (25°C)	0.89
Dropping Point, ASTM D-2265	569°F (298°C)
Flash Point, ASTM D-92	>400°F (>204°C)
Penetration, ASTM D-217 worked @ 77°F (25°C)	370
Base Oil Viscosity SUS @ 100°F (37°C)	2344
SUS @ 210°F (98°C)	110.8
Corrosion Preventive Properties, ASTM D-1743 @ 125°F (51°C)	Pass
Water Washout Characteristics ASTM D-1264 @ 100°F (37°C)	2.5
Evaporation Loss, ASTM D-972 @ 210°F (98°C)	0.69
Oxidation Stability, ASTM D-942 @ 210°F (98°C), 72 hrs. PSI Loss	3 psi
Shelf Life (unopened container)	Two years

### CONTAINER SIZE

Cart Case (40 cartridges)  
5 Gal (19 L)  
55 Gal (208 L)

Manufactured by  
**BALMAR, LLC**

616 WEST PONT DES MOULTON ROAD / LAFAYETTE, LA 70507-4002

Sales Locations:  
LAFAYETTE, LA - HOUSTON, TX - LONGVIEW TX - MIDLAND, TX - YUKON, OK

\*Registered Tradename of  
Oil Center Research, Inc.

Made in U.S.A.

© 2002, BALMAR, LLC

06/10/10