



Liquid-O-Ring®*

Your Super Center for over 1,000 top performance products serving industries worldwide.

1960 PREMIUM VALVE SEALANT

Liquid-O-Ring®

Anti-Seize
Compounds
Drill Collar and Tool
Joint Compounds
Extreme Temperature
Compounds
Fish Net Coatings
Greases
Bearing
Food Grade
High Temp
Low Temp
Multi-Purpose
Specialty
Silicone
Synthetic
Oils
Compressor
Cutting
Forging Die Lube
Gear
Hydraulic
Motor
Penetrating
Silicone
Torsion
Transmission
Treatment
Oilfield Production
Products
Pipe Storage
Compounds
Lubricants
Sealants
Pump Packings
Thread Cleaner
Thread Compounds
Biodegradable
High Temperature
Arctic Grade
Thread Locking
Compound
Thread Sealants
Valve Lubricants and
Sealants
Wireline Products

Protekto-Coat
Internal and External
Pipe Coatings
Low VOC
Biodegradable
Corrosion Inhibitors

Speciality Items
Cleaners and
Degreasers

PRODUCT DESCRIPTION

1960 Premium Valve Sealant is formulated for expanding gate type valve applications, however it is also effective on other valve types. This high temperature, high pressure sealant is great for applications under severe conditions including gases, distillates, weakened acids, and steam. **1960 Premium Valve Sealant** provides lubrication as it seals even in extreme applications.

BENEFITS

High temperature
High pressure
Great under severe conditions
Lubricates and seals
Reduces torque
Water Resistant
Pumpable
Non-toxic
Non-hazardous

APPLICATION

1960 Premium Valve Sealant is recommended for applications where peanut butter type products are not effective. Applications of **1960 Premium Valve Sealant** include oilfield production such as Christmas trees and line valves. **1960 Premium Valve Sealant** is also recommended for industrial and marine applications on gate valves where hydrocarbon or hydrocarbon/water resistance is required.

TYPICAL OBSERVATIONS

Color	Tan
Appearance	Sticky Paste
Thickener	Inorganic
Density, lb/gal @ 77°F (25°C)	9.15
Specific Gravity, @ 77°F (25°C)	1.10
Dropping Point, ASTM D-2265	None
Flash Point, ASTM D-92	>500°F (260°C)
Penetration, ASTM D-217 worked @ 77°F (25°C)	230 - 260
Oil Separation, wt. % ASTM D-6184	4.0 max
Temperature Range	-0°F to 400°F (-18°C to 204°C)

CONTAINER SIZE

Bulk
1 gal (4 L)
5 gal (19 L)
55 gal (208 L)
Stick
J-Stick Pak (16 sticks)
K-Stick Case (12 sticks)

RELATED PRODUCTS

For information on our complete line of valve related products contact us at www.oilcenter.com.

*Registered Tradename of Oil Center Research, Inc.

WARRANTY Because the conditions of use and the supervision of application are beyond our control, we assume no liability for any product failure or other damage beyond the purchase price of the material furnished by us. No agent, representative, or employee of this Company is authorized to change this provision, which relates to all goods delivered, whether sold, delivered as samples, or otherwise.

Made in U.S.A.

© 2002, BALMAR, LLC

Manufactured by

BALMAR, LLC

616 WEST PONT DES MOUTON ROAD / LAFAYETTE, LA 70507-4002

Sales Locations:

LAFAYETTE, LA - HOUSTON, TX - LONGVIEW, TX - MIDLAND, TX - YUKON, OK

04/12/07