

Lubon 404G

All Purpose Lubricant & Sealant

Made with Liquilon®

Lubon 404G is an all-purpose lubricant and sealant for applications that require the best lubrication available. Lubon 404G's processing and formulation enable it to provide a versatility not found in conventional lubricants. Lubon 404G may be used on brass, aluminum, copper, and stainless steel, as well as conventional steel threads.

Lubon 404G is made with Liquilon® which is inert and unaffected by acids, oils, caustics, and common solvents. It is used in applications with temperatures to >400°F (>204°C) and services pressures up to 10,000 psi. Lubon 404G gives long-lasting protection to coated parts, which keeps equipment in top operating condition.

Lubon 404G is recommended for the lubrication requirements of equipment that must be operated over extended periods of time or where shut downs are prohibitive. Equipment wear will be reduced and loss of lubrication will be stopped by the unique sealing characteristics of Lubon 404G. Lubon 404G possesses a unique plating and coating ability which provides a residual lubrication film that eliminates metal-to-metal contact and prevents rust and corrosion.

APPLICATION

The uses of Lubon 404G are varied. In general, Lubon 404G may be applied to threaded connections, gaskets, gear boxes, gear and chain drive units, draw works, direct rotary drives, outboard motor lower units, stop cocks, wellheads, swivel joints, and universal joints, as a pump and valve packing, and additive to truck rear ends.

BENEFITS

- Remains pliable
- Hydrogen sulfide resistant
- Could be applied to oily threads
- Reduces friction
- Seals leaking units
- Results in smoother operation
- Services temperatures to >400°F (>204°C) and pressures up to 10,000 psi



OIL CENTER RESEARCH INTERNATIONAL, L.L.C.

337.993.3559 | 800.549.2407 | www.oilcenter.com | info@oilcenter.com